

## CASTOR FHPK4WC080DAU5D0N



|                                  |                         |
|----------------------------------|-------------------------|
| <b>Product SKU</b>               | FHPK4WC080DAU5D0N       |
| <b>Standard Compliance</b>       | DIN EN 12533            |
| <b>Series</b>                    | DAU5                    |
| <b>Fastening</b>                 | Plate fastening         |
| <b>Brake and Direction</b>       | fixed direction         |
| <b>Material of the Wheel</b>     | aluminum wheel center   |
| <b>Tread</b>                     | polyurethane (PU) tread |
| <b>Temperature range</b>         | -20°C to +60°C          |
| <b>Wheel Diameter</b>            | 80mm                    |
| <b>Load Capacity</b>             | 180kg                   |
| <b>Total Hight</b>               | 120mm                   |
| <b>Width of Tread</b>            | 30mm                    |
| <b>wheel hub Width</b>           | 47mm                    |
| <b>Dimension of Plate</b>        | 100x88mm                |
| <b>Hole Spacing of the Plate</b> | 80/75x60/55/48mm        |
| <b>Wheel Bolt Size</b>           | M10                     |
| <b>Bushing Diameter</b>          | 15mm                    |
| <b>Wheel Bearing</b>             | double ball bearing     |
| <b>Rubber Shore</b>              | 95° Shore A             |





## CASTOR FHPK4WC080DAU5D0N

