



## CASTOR HAH15C0125P2T2B42



|                                     |                                 |
|-------------------------------------|---------------------------------|
| <b>Product SKU</b>                  | HAH15C0125P2T2B42               |
| <b>Standard Compliance</b>          | DIN EN 12530                    |
| <b>Series</b>                       | P2T2                            |
| <b>Fastening</b>                    | Bolt fastening                  |
| <b>Material of the Wheel</b>        | polypropylene (PP) wheel center |
| <b>Tread</b>                        | thermoplastic rubber tread      |
| <b>Temperature range</b>            | -20°C to +60°C                  |
| <b>Wheel Diameter</b>               | 125mm                           |
| <b>Load Capacity</b>                | 100kg                           |
| <b>Total Height</b>                 | 160mm                           |
| <b>Width of Tread</b>               | 32mm                            |
| <b>wheel hub Width</b>              | 36mm                            |
| <b>Offset</b>                       | 40mm                            |
| <b>Fastening Bolt Hole Diameter</b> | 11mm                            |
| <b>Wheel Bolt Size</b>              | M8                              |
| <b>Bushing Diameter</b>             | 8mm                             |
| <b>Weight</b>                       | 0.62kg                          |
| <b>Wheel Bearing</b>                | ball bearing                    |
| <b>Rubber Shore</b>                 | 95° Shore A                     |

