

## CASTOR BBH85WC125SWS4R0NE



|                                     |                     |
|-------------------------------------|---------------------|
| <b>Product SKU</b>                  | BBH85WC125SWS4R0NE  |
| <b>Standard Compliance</b>          | DIN EN 12532        |
| <b>Series</b>                       | SWS4 (ESD)          |
| <b>Fastening</b>                    | Bolt fastening      |
| <b>Brake and Direction</b>          | back brake          |
| <b>Material of the Wheel</b>        | steel wheel center  |
| <b>Tread</b>                        | solid rubber tread  |
| <b>Temperature range</b>            | -20°C to +60°C      |
| <b>Wheel Diameter</b>               | 125mm               |
| <b>Load Capacity</b>                | 70kg                |
| <b>Total Hight</b>                  | 154mm               |
| <b>Width of Tread</b>               | 37mm                |
| <b>wheel hub Width</b>              | 50mm                |
| <b>Offset</b>                       | 45mm                |
| <b>Fastening Bolt Hole Diameter</b> | 13mm                |
| <b>Swivel Radius</b>                | 127mm               |
| <b>Wheel Bolt Size</b>              | M10                 |
| <b>Bushing Diameter</b>             | 15mm                |
| <b>Weight</b>                       | 1.19kg              |
| <b>Wheel Bearing</b>                | roller bearing      |
| <b>Rubber Shore</b>                 | 85° Shore A         |
| <b>Special Features</b>             | electrostatic (ESD) |

