



## CASTOR SHP5EWC200Z4U5D34



|                                  |                             |
|----------------------------------|-----------------------------|
| <b>Product SKU</b>               | SHP5EWC200Z4U5D34           |
| <b>Standard Compliance</b>       | DIN EN 12533                |
| <b>Series</b>                    | Z4U5                        |
| <b>Fastening</b>                 | Plate fastening             |
| <b>Brake and Direction</b>       | swivel without brake        |
| <b>Material of the Wheel</b>     | polyamide (PA) wheel center |
| <b>Tread</b>                     | polyurethane (PU) tread     |
| <b>Temperature range</b>         | -20°C to +80°C              |
| <b>Wheel Diameter</b>            | 200mm                       |
| <b>Load Capacity</b>             | 500kg                       |
| <b>Total Hight</b>               | 245mm                       |
| <b>Width of Tread</b>            | 45mm                        |
| <b>wheel hub Width</b>           | 60mm                        |
| <b>Offset</b>                    | 55mm                        |
| <b>Dimension of Plate</b>        | 135x110mm                   |
| <b>Hole Spacing of the Plate</b> | 105x84/76mm                 |
| <b>Wheel Bolt Size</b>           | M12                         |
| <b>Bushing Diameter</b>          | 12mm                        |
| <b>Weight</b>                    | 2.59kg                      |
| <b>Wheel Bearing</b>             | double ball bearing         |
| <b>Rubber Shore</b>              | 94° Shore A                 |





## CASTOR SHP5EWC200Z4U5D34

