

## CASTOR SPP21WC100N4B5B34



|                                  |                             |
|----------------------------------|-----------------------------|
| <b>Product SKU</b>               | SPP21WC100N4B5B34           |
| <b>Standard Compliance</b>       | DIN EN 12532                |
| <b>Series</b>                    | N4B5                        |
| <b>Fastening</b>                 | Plate fastening             |
| <b>Brake and Direction</b>       | swivel without brake        |
| <b>Material of the Wheel</b>     | polyamide (PA) wheel center |
| <b>Tread</b>                     | polyurethane (PU) tread     |
| <b>Temperature range</b>         | -20°C to +80°C              |
| <b>Wheel Diameter</b>            | 100mm                       |
| <b>Load Capacity</b>             | 200kg                       |
| <b>Total Hight</b>               | 128mm                       |
| <b>Width of Tread</b>            | 32mm                        |
| <b>wheel hub Width</b>           | 40mm                        |
| <b>Offset</b>                    | 40mm                        |
| <b>Dimension of Plate</b>        | 105x80mm                    |
| <b>Hole Spacing of the Plate</b> | 80/77x60mm                  |
| <b>Wheel Bolt Size</b>           | M8                          |
| <b>Bushing Diameter</b>          | 8mm                         |
| <b>Weight</b>                    | 0.69kg                      |
| <b>Wheel Bearing</b>             | ball bearing                |
| <b>Rubber Shore</b>              | 92° Shore A                 |





## CASTOR SPP21WC100N4B5B34

