

## RATTAKOMPLEKT BAH15C0080P2T2B42



<b>Product SKU</b>	BAH15C0080P2T2B42, BAH15C0080P2T2B42
<b>Standard Compliance</b>	DIN EN 12530, DIN EN 12530
<b>Series</b>	P2T2, P2T2
<b>Fastening</b>	Bolt fastening, Bolt fastening
<b>Brake and Direction</b>	back brake, back brake
<b>Material of the Wheel</b>	polypropylene (PP) wheel center, polypropylene (PP) wheel center
<b>Tread</b>	thermoplastic rubber tread, thermoplastic rubber tread
<b>Temperature range</b>	-20°C to +60°C, -20°C to +60°C
<b>Wheel Diameter</b>	80mm, 80mm
<b>Load Capacity</b>	80kg, 80kg
<b>Total Hight</b>	111mm, 111mm
<b>Width of Tread</b>	32mm, 32mm
<b>wheel hub Width</b>	36mm, 36mm
<b>Offset</b>	37mm, 37mm
<b>Fastening Bolt Hole Diameter</b>	11mm, 11mm
<b>Swivel Radius</b>	132mm, 132mm
<b>Wheel Bolt Size</b>	M8, M8
<b>Bushing Diameter</b>	8mm, 8mm
<b>Weight</b>	0.63kg, 0.63kg
<b>Wheel Bearing</b>	ball bearing, ball bearing
<b>Rubber Shore</b>	95° Shore A, 95° Shore A



# RATTAKOMPLEKT BAH15C0080P2T2B42

