

## CASTOR SDPE6C0050N4N4P0N



|                                  |                             |
|----------------------------------|-----------------------------|
| <b>Product SKU</b>               | SDPE6C0050N4N4P0N           |
| <b>Standard Compliance</b>       | DIN EN 12530                |
| <b>Series</b>                    | N4N4                        |
| <b>Fastening</b>                 | Plate fastening             |
| <b>Brake and Direction</b>       | swivel without brake        |
| <b>Material of the Wheel</b>     | polyamide (PA) wheel center |
| <b>Tread</b>                     | polyamide (PA) tread        |
| <b>Temperature range</b>         | -20°C to +60°C              |
| <b>Wheel Diameter</b>            | 50mm                        |
| <b>Load Capacity</b>             | 70kg                        |
| <b>Total Hight</b>               | 70mm                        |
| <b>Width of Tread</b>            | 18mm                        |
| <b>wheel hub Width</b>           | 44mm                        |
| <b>Offset</b>                    | 25mm                        |
| <b>Dimension of Plate</b>        | 60x60mm                     |
| <b>Hole Spacing of the Plate</b> | 48/38x48/38mm               |
| <b>Wheel Bolt Size</b>           | M6                          |
| <b>Bushing Diameter</b>          | 8mm                         |
| <b>Weight</b>                    | 0.26kg                      |
| <b>Wheel Bearing</b>             | plain bearing               |

