




## RATTAKOMPLEKT SAPE5C0080P2T2P0N



<b>Product SKU</b>	SAPE5C0080P2T2P0N, SAPE5C0080P2T2P0N
<b>Standard Compliance</b>	DIN EN 12530, DIN EN 12530
<b>Series</b>	P2T2, P2T2
<b>Fastening</b>	Plate fastening, Plate fastening
<b>Brake and Direction</b>	swivel without brake, swivel without brake
<b>Material of the Wheel</b>	polypropylene (PP) wheel center, polypropylene (PP) wheel center
<b>Tread</b>	thermoplastic rubber tread, thermoplastic rubber tread
<b>Temperature range</b>	-20°C to +60°C, -20°C to +60°C
<b>Wheel Diameter</b>	80mm, 80mm
<b>Load Capacity</b>	80kg, 80kg
<b>Total Hight</b>	111mm, 111mm
<b>Width of Tread</b>	32mm, 32mm
<b>wheel hub Width</b>	36mm, 36mm
<b>Offset</b>	37mm, 37mm
<b>Dimension of Plate</b>	77x67mm, 77x67mm
<b>Hole Spacing of the Plate</b>	61.5/56x51.5/46.5mm, 61.5/56x51.5/46.5mm
<b>Wheel Bolt Size</b>	M8, M8
<b>Bushing Diameter</b>	12mm, 12mm
<b>Weight</b>	0.41kg, 0.41kg
<b>Wheel Bearing</b>	plain bearing, plain bearing
<b>Rubber Shore</b>	95° Shore A, 95° Shore A



# RATTAKOMPLEKT SAPE5C0080P2T2P0N

