


## RATTAKOMPLEKT FBP22WC100P0P0P0N



<b>Product SKU</b>	FBP22WC100P0P0P0N, FBP22WC100P0P0P0N
<b>Standard Compliance</b>	DIN EN 12532, DIN EN 12532
<b>Series</b>	P0P0, P0P0
<b>Fastening</b>	Plate fastening, Plate fastening
<b>Brake and Direction</b>	fixed direction, fixed direction
<b>Material of the Wheel</b>	polypropylene (PP) wheel center, polypropylene (PP) wheel center
<b>Tread</b>	polypropylene (PP) tread, polypropylene (PP) tread
<b>Temperature range</b>	-20°C to +60°C, -20°C to +60°C
<b>Wheel Diameter</b>	100mm, 100mm
<b>Load Capacity</b>	100kg, 100kg
<b>Total Hight</b>	125mm, 125mm
<b>Width of Tread</b>	36mm, 36mm
<b>wheel hub Width</b>	40mm, 40mm
<b>Dimension of Plate</b>	105x80mm, 105x80mm
<b>Hole Spacing of the Plate</b>	80/77x60mm, 80/77x60mm
<b>Wheel Bolt Size</b>	M8, M8
<b>Bushing Diameter</b>	12mm, 12mm
<b>Weight</b>	0.37kg, 0.37kg
<b>Wheel Bearing</b>	plain bearing, plain bearing



## RATTAKOMPLEKT FBP22WC100P0P0P0N

