


## RATTAKOMPLEKT SPP47WC125N0N0B30



<b>Product SKU</b>	SPP47WC125N0N0B30, SPP47WC125N0N0B30
<b>Standard Compliance</b>	DIN EN 12532, DIN EN 12532
<b>Series</b>	N0N0, N0N0
<b>Fastening</b>	Plate fastening, Plate fastening
<b>Brake and Direction</b>	swivel without brake, swivel without brake
<b>Material of the Wheel</b>	polyamide (PA) wheel center, polyamide (PA) wheel center
<b>Tread</b>	polyamide (PA) tread, polyamide (PA) tread
<b>Temperature range</b>	-40°C to +80°C, -40°C to +80°C
<b>Wheel Diameter</b>	125mm, 125mm
<b>Load Capacity</b>	200kg, 200kg
<b>Total Hight</b>	155mm, 155mm
<b>Width of Tread</b>	38mm, 38mm
<b>wheel hub Width</b>	50mm, 50mm
<b>Offset</b>	50mm, 50mm
<b>Dimension of Plate</b>	135x110mm, 135x110mm
<b>Hole Spacing of the Plate</b>	105x84/76mm, 105x84/76mm
<b>Wheel Bolt Size</b>	M10, M10
<b>Bushing Diameter</b>	10mm, 10mm
<b>Weight</b>	1.32kg, 1.32kg
<b>Wheel Bearing</b>	ball bearing, ball bearing



# RATTAKOMPLEKT SPP47WC125N0N0B30

