

## RATTAKOMPLEKT SAPA2C0075P2T2P0NE



|                                  |                                 |
|----------------------------------|---------------------------------|
| <b>Product SKU</b>               | SAPA2C0075P2T2P0NE              |
| <b>Standard Compliance</b>       | DIN EN 12530                    |
| <b>Series</b>                    | P2T2 (ESD)                      |
| <b>Fastening</b>                 | Plate fastening                 |
| <b>Material of the Wheel</b>     | polypropylene (PP) wheel center |
| <b>Tread</b>                     | thermoplastic rubber tread      |
| <b>Temperature range</b>         | -20°C to +60°C                  |
| <b>Wheel Diameter</b>            | 75mm                            |
| <b>Load Capacity</b>             | 50kg                            |
| <b>Total Hight</b>               | 100mm                           |
| <b>Width of Tread</b>            | 25mm                            |
| <b>wheel hub Width</b>           | 28mm                            |
| <b>Offset</b>                    | 25mm                            |
| <b>Dimension of Plate</b>        | 60x60mm                         |
| <b>Hole Spacing of the Plate</b> | 48/38x48/38mm                   |
| <b>Wheel Bolt Size</b>           | M6                              |
| <b>Bushing Diameter</b>          | 8mm                             |
| <b>Weight</b>                    | 0.23kg                          |
| <b>Wheel Bearing</b>             | plain bearing                   |
| <b>Special Features</b>          | electrostatic (ESD)             |

