


## CASTOR FIP32SC125C4C4L0N



|                                  |   |
|----------------------------------|---|
| <b>Product SKU</b>               | FIP32SC125C4C4L0N                           |
| <b>Standard Compliance</b>       | DIN EN 12532                                |
| <b>Series</b>                    | C4C4  |
| <b>Fastening</b>                 | Plate fastening                             |
| <b>Brake and Direction</b>       | fixed direction                             |
| <b>Material of the Wheel</b>     | polyamide (PA) with fiberglass wheel center |
| <b>Tread</b>                     | polyamide (PA) with fiberglass tread        |
| <b>Temperature range</b>         | -20°C to +280°C                             |
| <b>Wheel Diameter</b>            | 125mm                                       |
| <b>Load Capacity</b>             | 130kg                                       |
| <b>Total Height</b>              | 155mm                                       |
| <b>Width of Tread</b>            | 31mm  |
| <b>wheel hub Width</b>           | 52mm  |
| <b>Dimension of Plate</b>        | 100x80mm                                    |
| <b>Hole Spacing of the Plate</b> | 80/72x60/52mm                               |
| <b>Wheel Bolt Size</b>           | M8  |
| <b>Bushing Diameter</b>          | 12mm  |
| <b>Wheel Bearing</b>             | plain bearing                               |
| <b>Special Features</b>          | heat-resistant                              |





## CASTOR FIP32SC125C4C4L0N

