

## CASTOR LGTK4WC200N2U6P0N



|                              |                             |
|------------------------------|-----------------------------|
| <b>Product SKU</b>           | LGTK4WC200N2U6P0N           |
| <b>Standard Compliance</b>   | DIN EN 12532                |
| <b>Series</b>                | N2U6                        |
| <b>Fastening</b>             | Stem fastening              |
| <b>Material of the Wheel</b> | polyamide (PA) wheel center |
| <b>Tread</b>                 | polyurethane (PU) tread     |
| <b>Temperature range</b>     | -40°C to +80°C              |
| <b>Wheel Diameter</b>        | 200mm                       |
| <b>Load Capacity</b>         | 700kg                       |
| <b>Total Height</b>          | 241mm                       |
| <b>Width of Tread</b>        | 50mm                        |
| <b>wheel hub Width</b>       | 63mm                        |
| <b>Offset</b>                | 40mm                        |
| <b>Swivel Radius</b>         | 276.5mm                     |
| <b>Wheel Bolt Size</b>       | M12                         |
| <b>Bushing Diameter</b>      | 20mm                        |
| <b>Wheel Bearing</b>         | plain bearing               |
| <b>Rubber Shore</b>          | 95° Shore A                 |



# CASTOR LGTK4WC200N2U6P0N

