

RATTAKOMPLEKT BAH15C0150P2T2P0N



Toote SKU	BAH15C0150P2T2P0N, BAH15C0150P2T2P0N
EU toote vastavus	DIN EN 12530, DIN EN 12530
Seeria	P2T2, P2T2
Kinnitus	Poltkinnitussega, Poltkinnitussega
Pidur ja jooks	tagapiduriga, tagapiduriga
Ratta keskosa materjal	ratta keskosa polüpropüleen (PP), ratta keskosa polüpropüleen (PP)
Turvise materjal	turvis termoplastiline kumm, turvis termoplastiline kumm
Soovituslik kasutustemperatuur	-20°C kuni +60°C, -20°C kuni +60°C vahemik
Ratta diameeter	150mm, 150mm
Kandevõime	100kg, 100kg
Kogukõrgus	185mm, 185mm
Turvise laius	32mm, 32mm
Ratta rummu laius	36mm, 36mm
Offset	40mm, 40mm
Kinnituspoldi läbimõõt	11mm, 11mm
Pöörderaadius	132mm, 132mm
Ratta poldi läbimõõt	M8, M8
Puksi diameeter	12mm, 12mm
Ratta laager	liuglaager, liuglaager
Kummi kõvadus	95° Shore A, 95° Shore A





RATTAKOMPLEKT BAH15C0150P2T2P0N

