

RATTAKOMPLEKT TPP58WC200P0P0P0N



Toote SKU	TPP58WC200P0P0P0N, TPP58WC200P0P0P0N
EU toote vastavus	DIN EN 12532, DIN EN 12532
Seeria	P0P0, P0P0
Kinnitus	Plaatkinnitusega, Plaatkinnitusega
Pidur ja jooks	tagapiduriga, tagapiduriga
Ratta keskosa materjal	ratta keskosa polüpropüleen (PP), ratta keskosa polüpropüleen (PP)
Turvise materjal	turvise polüpropüleen (PP), turvis polüpropüleen (PP)
Soovituslik kasutustemperatuur	-20°C kuni +60°C, -20°C kuni +60°C vahemik
Ratta diameeter	200mm, 200mm
Kandevõime	250kg, 250kg
Kogukõrgus	235mm, 235mm
Turvise laius	50mm, 50mm
Ratta rummu laius	59mm, 59mm
Offset	55mm, 55mm
Kinnitusplaadi mõõdud	135x110mm, 135x110mm
Kinnitusavade kaugused	105x84/76mm, 105x84/76mm
Pöörderaadius	165mm, 165mm
Ratta poldi läbimõõt	M12, M12
Puksi diameeter	20mm, 20mm
Kaal	2.2kg, 2.2kg
Ratta laager	liuglaager, liuglaager

