


## RATTAKOMPLEKT SPP27WC100AAB5D39



|                                  |                          |
|----------------------------------|--------------------------|
| <b>Product SKU</b>               | SPP27WC100AAB5D39        |
| <b>Standard Compliance</b>       | DIN EN 12532             |
| <b>Series</b>                    | AAB5                     |
| <b>Fastening</b>                 | Plaatkinnitusega         |
| <b>Brake and Direction</b>       | pöörlev ilma pidurita    |
| <b>Material of the Wheel</b>     | ratta keskosa alumiinium |
| <b>Tread</b>                     | turvis polüuretaan (PU)  |
| <b>Temperature range</b>         | -20°C kuni +80°C         |
| <b>Wheel Diameter</b>            | 100mm                    |
| <b>Load Capacity</b>             | 180kg                    |
| <b>Total Hight</b>               | 128mm                    |
| <b>Width of Tread</b>            | 32mm                     |
| <b>wheel hub Width</b>           | 40mm                     |
| <b>Offset</b>                    | 40mm                     |
| <b>Dimension of Plate</b>        | 105x80mm                 |
| <b>Hole Spacing of the Plate</b> | 80/77x60mm               |
| <b>Wheel Bolt Size</b>           | M8                       |
| <b>Bushing Diameter</b>          | 8mm                      |
| <b>Weight</b>                    | 0.86kg                   |
| <b>Wheel Bearing</b>             | topelt kuullaager        |
| <b>Rubber Shore</b>              | 92° Shore A              |



## RATTAKOMPLEKT SPP27WC100AAB5D39

