


RATTAKOMPLEKT TBP25WC100P0P0P0N



Toote SKU	TBP25WC100P0P0P0P0N, TBP25WC100P0P0P0P0N
EU toote vastavus	DIN EN 12532, DIN EN 12532
Seeria	P0P0, P0P0
Kinnitus	Plaatkinnitusega, Plaatkinnitusega
Pidur ja jooks	tagapiduriga, tagapiduriga
Ratta keskosa materjal	ratta keskosa polüpropüleen (PP), ratta keskosa polüpropüleen (PP)
Turvise materjal	turvise polüpropüleen (PP), turvis polüpropüleen (PP)
Soovituslik kasutustemperatuur	-20°C kuni +60°C, -20°C kuni +60°C vahemik
Ratta diameeter	100mm, 100mm
Kandevõime	100kg, 100kg
Kogukõrgus	125mm, 125mm
Turvise laius	36mm, 36mm
Ratta rummu laius	40mm, 40mm
Offset	40mm, 40mm
Kinnitusplaadi mõõdud	105x80mm, 105x80mm
Kinnitusavade kaugused	80/77x60mm, 80/77x60mm
Pöörderaadius	127mm, 127mm
Ratta poldi läbimõõt	M8, M8
Puksi diameeter	12mm, 12mm
Kaal	0.73kg, 0.73kg
Ratta laager	liuglaager, liuglaager



RATTAKOMPLEKT TBP25WC100P0P0P0N

