

RATTAKOMPLEKT TDPE6C0050P2T2P0N



Product SKU	TDPE6C0050P2T2P0N, TDPE6C0050P2T2P0N
Standard Compliance	DIN EN 12530, DIN EN 12530
Series	P2T2, P2T2
Fastening	Plaatkinnitusega, Plaatkinnitusega
Brake and Direction	tagapiduriga, tagapiduriga
Material of the Wheel	ratta keskosa polüpropüleen (PP), ratta keskosa polüpropüleen (PP)
Tread	turvis termoplastiline kumm, turvis termoplastiline kumm
Temperature range	-20°C kuni +60°C, -20°C kuni +60°C
Wheel Diameter	50mm, 50mm
Load Capacity	70kg, 70kg
Total Hight	70mm, 70mm
Width of Tread	19mm, 19mm
wheel hub Width	44mm, 44mm
Offset	25mm, 25mm
Dimension of Plate	60x60mm, 60x60mm
Hole Spacing of the Plate	48/38×48/38mm, 48/38×48/38mm
Swivel Radius	80mm, 80mm
Wheel Bolt Size	M6, M6
Bushing Diameter	8mm, 8mm
Weight	0.33kg, 0.33kg
Wheel Bearing	liuglaager, liuglaager
Rubber Shore	95° Shore A, 95° Shore A



RATTAKOMPLEKT TDPE6C0050P2T2P0N

