

CASTOR BAH15C0100P2T2B42E



Standard ComplianceDIN EN 12530SeriesP2T2 (ESD)FasteningBolt fasteningBrake and Directionback brakeMaterial of the Wheelpolypropylene (PP) wheel centerTreadthermoplastic rubber treadTemperature ange-20°C to +60°C
FasteningBolt fasteningBrake and Directionback brakeMaterial of the Wheelpolypropylene (PP) wheel centerTreadthermoplastic rubber treadTemperature-20°C to ±60°C
Brake and Directionback brakeMaterial of the Wheelpolypropylene (PP) wheel centerTreadthermoplastic rubber treadTemperature-20°C to ±60°C
DirectionDack brakeMaterial of the Wheelpolypropylene (PP) wheel centerTreadthermoplastic rubber treadTemperature-20°C to ±60°C
Wheelpolypropylene (PP) wheel centerTreadthermoplastic rubber treadTemperature-20°C to +60°C
Temperature -20°C to +60°C
Wheel Diameter 100mm
Load Capacity 70kg
Total Hight 135mm
Width of Tread 32mm
wheel hub Width 36mm
Offset 37mm
Fastening Bolt Hole Diameter 11mm
Swivel Radius 132mm
Wheel Bolt Size M8
Bushing 8mm Diameter
Wheel Bearing ball bearing
Special Features electrostatic (ESD)



www.cascoo.ee