

## CASTOR BAH15C0100P2T2P0NA



|                                     |                                 |
|-------------------------------------|---------------------------------|
| <b>Product SKU</b>                  | BAH15C0100P2T2P0NA              |
| <b>Standard Compliance</b>          | DIN EN 12530                    |
| <b>Series</b>                       | P2T2 (antistatic)               |
| <b>Fastening</b>                    | Bolt fastening                  |
| <b>Brake and Direction</b>          | back brake                      |
| <b>Material of the Wheel</b>        | polypropylene (PP) wheel center |
| <b>Tread</b>                        | thermoplastic rubber tread      |
| <b>Temperature range</b>            | -20°C to +60°C                  |
| <b>Wheel Diameter</b>               | 100mm                           |
| <b>Load Capacity</b>                | 70kg                            |
| <b>Total Hight</b>                  | 135mm                           |
| <b>Width of Tread</b>               | 32mm                            |
| <b>wheel hub Width</b>              | 36mm                            |
| <b>Offset</b>                       | 37mm                            |
| <b>Fastening Bolt Hole Diameter</b> | 11mm                            |
| <b>Swivel Radius</b>                | 132mm                           |
| <b>Wheel Bolt Size</b>              | M8                              |
| <b>Bushing Diameter</b>             | 12mm                            |
| <b>Weight</b>                       | 0.65kg                          |
| <b>Wheel Bearing</b>                | plain bearing                   |
| <b>Special Features</b>             | antistatic                      |

