

## CASTOR BBH35WC100P4S4R0NA



|                                     |                                 |
|-------------------------------------|---------------------------------|
| <b>Product SKU</b>                  | BBH35WC100P4S4R0NA              |
| <b>Standard Compliance</b>          | DIN EN 12532                    |
| <b>Series</b>                       | P4S4 (antistatic)               |
| <b>Fastening</b>                    | Bolt fastening                  |
| <b>Brake and Direction</b>          | back brake                      |
| <b>Material of the Wheel</b>        | polypropylene (PP) wheel center |
| <b>Tread</b>                        | solid rubber tread              |
| <b>Temperature range</b>            | -20°C to +60°C                  |
| <b>Wheel Diameter</b>               | 100mm                           |
| <b>Load Capacity</b>                | 50kg                            |
| <b>Total Hight</b>                  | 124mm                           |
| <b>Width of Tread</b>               | 32mm                            |
| <b>wheel hub Width</b>              | 40mm                            |
| <b>Offset</b>                       | 40mm                            |
| <b>Fastening Bolt Hole Diameter</b> | 13mm                            |
| <b>Swivel Radius</b>                | 127mm                           |
| <b>Wheel Bolt Size</b>              | M8                              |
| <b>Bushing Diameter</b>             | 12mm                            |
| <b>Weight</b>                       | 0.83kg                          |
| <b>Wheel Bearing</b>                | roller bearing                  |
| <b>Rubber Shore</b>                 | 85° Shore A                     |
| <b>Special Features</b>             | antistatic                      |

