

## CASTOR BIH36SC080N2U6Q0N



|                                     |                             |
|-------------------------------------|-----------------------------|
| <b>Product SKU</b>                  | BIH36SC080N2U6Q0N           |
| <b>Standard Compliance</b>          | DIN EN 12532                |
| <b>Series</b>                       | N2U6                        |
| <b>Fastening</b>                    | Bolt fastening              |
| <b>Brake and Direction</b>          | back brake                  |
| <b>Material of the Wheel</b>        | polyamide (PA) wheel center |
| <b>Tread</b>                        | polyurethane (PU) tread     |
| <b>Temperature range</b>            | -40°C to +80°C              |
| <b>Wheel Diameter</b>               | 80mm                        |
| <b>Load Capacity</b>                | 130kg                       |
| <b>Total Hight</b>                  | 106mm                       |
| <b>Width of Tread</b>               | 32mm                        |
| <b>wheel hub Width</b>              | 40mm                        |
| <b>Offset</b>                       | 36mm                        |
| <b>Fastening Bolt Hole Diameter</b> | 13mm                        |
| <b>Swivel Radius</b>                | 115mm                       |
| <b>Wheel Bolt Size</b>              | M8                          |
| <b>Bushing Diameter</b>             | 12mm                        |
| <b>Wheel Bearing</b>                | roller bearing              |
| <b>Special Features</b>             | stainless steel             |





## CASTOR BIH36SC080N2U6Q0N

