

## CASTOR BPH87WC100AAE2D0N



|                                     |                       |
|-------------------------------------|-----------------------|
| <b>Product SKU</b>                  | BPH87WC100AAE2D0N     |
| <b>Standard Compliance</b>          | DIN EN 12532          |
| <b>Series</b>                       | AAE2                  |
| <b>Fastening</b>                    | Bolt fastening        |
| <b>Brake and Direction</b>          | back brake            |
| <b>Material of the Wheel</b>        | aluminum wheel center |
| <b>Tread</b>                        | elastic tread         |
| <b>Temperature range</b>            | -20°C to +80°C        |
| <b>Wheel Diameter</b>               | 100mm                 |
| <b>Load Capacity</b>                | 200kg                 |
| <b>Total Hight</b>                  | 127mm                 |
| <b>Width of Tread</b>               | 40mm                  |
| <b>wheel hub Width</b>              | 50mm                  |
| <b>Offset</b>                       | 40mm                  |
| <b>Fastening Bolt Hole Diameter</b> | 13mm                  |
| <b>Swivel Radius</b>                | 127mm                 |
| <b>Wheel Bolt Size</b>              | M8                    |
| <b>Bushing Diameter</b>             | 12mm                  |
| <b>Weight</b>                       | 1.11kg                |
| <b>Wheel Bearing</b>                | double ball bearing   |
| <b>Rubber Shore</b>                 | 65° Shore A           |

