

## CASTOR BPH87WC100AAU5D0N



|                                     |                         |
|-------------------------------------|-------------------------|
| <b>Product SKU</b>                  | BPH87WC100AAU5D0N       |
| <b>Standard Compliance</b>          | DIN EN 12532            |
| <b>Series</b>                       | AAU5                    |
| <b>Fastening</b>                    | Bolt fastening          |
| <b>Brake and Direction</b>          | back brake              |
| <b>Material of the Wheel</b>        | aluminum wheel center   |
| <b>Tread</b>                        | polyurethane (PU) tread |
| <b>Temperature range</b>            | -20°C to +60°C          |
| <b>Wheel Diameter</b>               | 100mm                   |
| <b>Load Capacity</b>                | 200kg                   |
| <b>Total Height</b>                 | 127mm                   |
| <b>Width of Tread</b>               | 40mm                    |
| <b>wheel hub Width</b>              | 50mm                    |
| <b>Offset</b>                       | 40mm                    |
| <b>Fastening Bolt Hole Diameter</b> | 13mm                    |
| <b>Swivel Radius</b>                | 127mm                   |
| <b>Wheel Bolt Size</b>              | M8                      |
| <b>Bushing Diameter</b>             | 12mm                    |
| <b>Weight</b>                       | 1.1kg                   |
| <b>Wheel Bearing</b>                | double ball bearing     |
| <b>Rubber Shore</b>                 | 92° Shore A             |

