


## CASTOR FBP22WC100P2V2B32



|                                  |                                 |
|----------------------------------|---------------------------------|
| <b>Product SKU</b>               | FBP22WC100P2V2B32               |
| <b>Standard Compliance</b>       | DIN EN 12532                    |
| <b>Series</b>                    | P2V2                            |
| <b>Fastening</b>                 | Plate fastening                 |
| <b>Brake and Direction</b>       | fixed direction                 |
| <b>Material of the Wheel</b>     | polypropylene (PP) wheel center |
| <b>Tread</b>                     | thermoplastic rubber tread      |
| <b>Temperature range</b>         | -20°C to +60°C                  |
| <b>Wheel Diameter</b>            | 100mm                           |
| <b>Load Capacity</b>             | 100kg                           |
| <b>Total Hight</b>               | 125mm                           |
| <b>Width of Tread</b>            | 32mm                            |
| <b>wheel hub Width</b>           | 40mm                            |
| <b>Dimension of Plate</b>        | 105x80mm                        |
| <b>Hole Spacing of the Plate</b> | 80/77x60mm                      |
| <b>Wheel Bolt Size</b>           | M8                              |
| <b>Bushing Diameter</b>          | 8mm                             |
| <b>Weight</b>                    | 0.45kg                          |
| <b>Wheel Bearing</b>             | ball bearing                    |
| <b>Rubber Shore</b>              | 85° Shore A                     |





## CASTOR FBP22WC100P2V2B32

