



## CASTOR FHP54WC200BAY5D0N



|                                  |                              |
|----------------------------------|------------------------------|
| <b>Product SKU</b>               | FHP54WC200BAY5D0N            |
| <b>Standard Compliance</b>       | DIN EN 12533                 |
| <b>Series</b>                    | BAY5                         |
| <b>Fastening</b>                 | Plate fastening              |
| <b>Brake and Direction</b>       | fixed direction              |
| <b>Material of the Wheel</b>     | aluminum wheel center        |
| <b>Tread</b>                     | PU-lastic/polyurethane tread |
| <b>Temperature range</b>         | -20°C to +60°C               |
| <b>Wheel Diameter</b>            | 200mm                        |
| <b>Load Capacity</b>             | 700kg                        |
| <b>Total Hight</b>               | 245mm                        |
| <b>Width of Tread</b>            | 50mm                         |
| <b>wheel hub Width</b>           | 60mm                         |
| <b>Dimension of Plate</b>        | 135x110mm                    |
| <b>Hole Spacing of the Plate</b> | 105x84/76mm                  |
| <b>Wheel Bolt Size</b>           | M12                          |
| <b>Bushing Diameter</b>          | 20mm                         |
| <b>Wheel Bearing</b>             | double ball bearing          |
| <b>Rubber Shore</b>              | 75° Shore A                  |

