

## CASTOR FIP55SC160N0N0L0N



|                                  |                             |
|----------------------------------|-----------------------------|
| <b>Product SKU</b>               | FIP55SC160N0N0L0N           |
| <b>Standard Compliance</b>       | DIN EN 12532                |
| <b>Series</b>                    | N0N0                        |
| <b>Fastening</b>                 | Plate fastening             |
| <b>Brake and Direction</b>       | fixed direction             |
| <b>Material of the Wheel</b>     | polyamide (PA) wheel center |
| <b>Tread</b>                     | polyamide (PA) tread        |
| <b>Temperature range</b>         | -40°C to +80°C              |
| <b>Wheel Diameter</b>            | 160mm                       |
| <b>Load Capacity</b>             | 300kg                       |
| <b>Total Hight</b>               | 195mm                       |
| <b>Width of Tread</b>            | 50mm                        |
| <b>wheel hub Width</b>           | 59mm                        |
| <b>Dimension of Plate</b>        | 135x110mm                   |
| <b>Hole Spacing of the Plate</b> | 105x76/84mm                 |
| <b>Wheel Bolt Size</b>           | M12                         |
| <b>Bushing Diameter</b>          | 20mm                        |
| <b>Weight</b>                    | 1.13kg                      |
| <b>Wheel Bearing</b>             | plain bearing               |
| <b>Special Features</b>          | stainless steel             |

