

## CASTOR FPP55WC160SWS4R0NA



|                                  |                    |
|----------------------------------|--------------------|
| <b>Product SKU</b>               | FPP55WC160SWS4R0NA |
| <b>Standard Compliance</b>       | DIN EN 12532       |
| <b>Series</b>                    | SWS4 (antistatic)  |
| <b>Fastening</b>                 | Plate fastening    |
| <b>Brake and Direction</b>       | fixed direction    |
| <b>Material of the Wheel</b>     | steel wheel center |
| <b>Tread</b>                     | solid rubber tread |
| <b>Temperature range</b>         | -20°C to +60°C     |
| <b>Wheel Diameter</b>            | 160mm              |
| <b>Load Capacity</b>             | 90kg               |
| <b>Total Hight</b>               | 195mm              |
| <b>Width of Tread</b>            | 40mm               |
| <b>wheel hub Width</b>           | 59mm               |
| <b>Dimension of Plate</b>        | 135x110mm          |
| <b>Hole Spacing of the Plate</b> | 105x84/76mm        |
| <b>Wheel Bolt Size</b>           | M12                |
| <b>Bushing Diameter</b>          | 20mm               |
| <b>Weight</b>                    | 1.76kg             |
| <b>Wheel Bearing</b>             | roller bearing     |
| <b>Rubber Shore</b>              | 85° Shore A        |
| <b>Special Features</b>          | antistatic         |

