

## CASTOR HBH85WC125P0P0R1W



|                                     |                                 |
|-------------------------------------|---------------------------------|
| <b>Product SKU</b>                  | HBH85WC125P0P0R1W               |
| <b>Standard Compliance</b>          | DIN EN 12532                    |
| <b>Series</b>                       | P0P0                            |
| <b>Fastening</b>                    | Bolt fastening                  |
| <b>Material of the Wheel</b>        | polypropylene (PP) wheel center |
| <b>Tread</b>                        | polypropylene (PP) tread        |
| <b>Temperature range</b>            | -20°C to +60°C                  |
| <b>Wheel Diameter</b>               | 125mm                           |
| <b>Load Capacity</b>                | 150kg                           |
| <b>Total Hight</b>                  | 154mm                           |
| <b>Width of Tread</b>               | 38mm                            |
| <b>wheel hub Width</b>              | 50mm                            |
| <b>Offset</b>                       | 40mm                            |
| <b>Fastening Bolt Hole Diameter</b> | 13mm                            |
| <b>Wheel Bolt Size</b>              | M10                             |
| <b>Bushing Diameter</b>             | 15mm                            |
| <b>Weight</b>                       | 0.7kg                           |
| <b>Wheel Bearing</b>                | roller bearing                  |





## CASTOR HBH85WC125P0P0R1W

