



## CASTOR HBH85WC125SWR2R0N



|                                     |                    |
|-------------------------------------|--------------------|
| <b>Product SKU</b>                  | HBH85WC125SWR2R0N  |
| <b>Standard Compliance</b>          | DIN EN 12532       |
| <b>Series</b>                       | SWR2               |
| <b>Fastening</b>                    | Bolt fastening     |
| <b>Material of the Wheel</b>        | steel wheel center |
| <b>Tread</b>                        | solid rubber tread |
| <b>Temperature range</b>            | -20°C to +60°C     |
| <b>Wheel Diameter</b>               | 125mm              |
| <b>Load Capacity</b>                | 100kg              |
| <b>Total Height</b>                 | 154mm              |
| <b>Width of Tread</b>               | 37mm               |
| <b>wheel hub Width</b>              | 50mm               |
| <b>Offset</b>                       | 40mm               |
| <b>Fastening Bolt Hole Diameter</b> | 13mm               |
| <b>Wheel Bolt Size</b>              | M10                |
| <b>Bushing Diameter</b>             | 15mm               |
| <b>Weight</b>                       | 1.02kg             |
| <b>Wheel Bearing</b>                | roller bearing     |
| <b>Rubber Shore</b>                 | 85° Shore A        |

CASCOO





## CASTOR HBH85WC125SWR2R0N

