

**CASTOR HDHHHC0050N4N4P0N**

|                                     |                             |
|-------------------------------------|-----------------------------|
| <b>Product SKU</b>                  | HDHHHC0050N4N4P0N           |
| <b>Standard Compliance</b>          | DIN EN 12530                |
| <b>Series</b>                       | N4N4                        |
| <b>Fastening</b>                    | Bolt fastening              |
| <b>Material of the Wheel</b>        | polyamide (PA) wheel center |
| <b>Tread</b>                        | polyamide (PA) tread        |
| <b>Temperature range</b>            | -20°C to +60°C              |
| <b>Wheel Diameter</b>               | 50mm                        |
| <b>Load Capacity</b>                | 70kg                        |
| <b>Total Height</b>                 | 70mm                        |
| <b>Width of Tread</b>               | 18mm                        |
| <b>wheel hub Width</b>              | 44mm                        |
| <b>Offset</b>                       | 25mm                        |
| <b>Fastening Bolt Hole Diameter</b> | 11mm                        |
| <b>Wheel Bolt Size</b>              | M6                          |
| <b>Bushing Diameter</b>             | 8mm                         |
| <b>Weight</b>                       | 0.21kg                      |
| <b>Wheel Bearing</b>                | plain bearing               |

