

## CASTOR HDHHHC0050P2T2P0N



|                                     |                                 |
|-------------------------------------|---------------------------------|
| <b>Product SKU</b>                  | HDHHHC0050P2T2P0N               |
| <b>Standard Compliance</b>          | DIN EN 12530                    |
| <b>Series</b>                       | P2T2                            |
| <b>Fastening</b>                    | Bolt fastening                  |
| <b>Material of the Wheel</b>        | polypropylene (PP) wheel center |
| <b>Tread</b>                        | thermoplastic rubber tread      |
| <b>Temperature range</b>            | -20°C to +60°C                  |
| <b>Wheel Diameter</b>               | 50mm                            |
| <b>Load Capacity</b>                | 70kg                            |
| <b>Total Height</b>                 | 70mm                            |
| <b>Width of Tread</b>               | 19mm                            |
| <b>wheel hub Width</b>              | 44mm                            |
| <b>Offset</b>                       | 25mm                            |
| <b>Fastening Bolt Hole Diameter</b> | 11mm                            |
| <b>Wheel Bolt Size</b>              | M6                              |
| <b>Bushing Diameter</b>             | 8mm                             |
| <b>Weight</b>                       | 0.2kg                           |
| <b>Wheel Bearing</b>                | plain bearing                   |
| <b>Rubber Shore</b>                 | 95° Shore A                     |





# CASTOR HDHHHC0050P2T2P0N

