



## CASTOR HPH98WC160P2G2B32



|                                     |                                 |
|-------------------------------------|---------------------------------|
| <b>Product SKU</b>                  | HPH98WC160P2G2B32               |
| <b>Standard Compliance</b>          | DIN EN 12532                    |
| <b>Series</b>                       | P2G2                            |
| <b>Fastening</b>                    | Bolt fastening                  |
| <b>Material of the Wheel</b>        | polypropylene (PP) wheel center |
| <b>Tread</b>                        | thermoplastic rubber tread      |
| <b>Temperature range</b>            | -20°C to +60°C                  |
| <b>Wheel Diameter</b>               | 160mm                           |
| <b>Load Capacity</b>                | 200kg                           |
| <b>Total Height</b>                 | 189mm                           |
| <b>Width of Tread</b>               | 40mm                            |
| <b>wheel hub Width</b>              | 59mm                            |
| <b>Offset</b>                       | 55mm                            |
| <b>Fastening Bolt Hole Diameter</b> | 13mm                            |
| <b>Wheel Bolt Size</b>              | M12                             |
| <b>Bushing Diameter</b>             | 12mm                            |
| <b>Weight</b>                       | 1.41kg                          |
| <b>Wheel Bearing</b>                | ball bearing                    |
| <b>Rubber Shore</b>                 | 70° Shore A                     |

