

## CASTOR HPH98WC160R4E2D34



|                                     |                             |
|-------------------------------------|-----------------------------|
| <b>Product SKU</b>                  | HPH98WC160R4E2D34           |
| <b>Standard Compliance</b>          | DIN EN 12532                |
| <b>Series</b>                       | R4E2                        |
| <b>Fastening</b>                    | Bolt fastening              |
| <b>Material of the Wheel</b>        | polyamide (PA) wheel center |
| <b>Tread</b>                        | elastic tread               |
| <b>Temperature range</b>            | -20°C to +80°C              |
| <b>Wheel Diameter</b>               | 160mm                       |
| <b>Load Capacity</b>                | 250kg                       |
| <b>Total Height</b>                 | 189mm                       |
| <b>Width of Tread</b>               | 46mm                        |
| <b>wheel hub Width</b>              | 59mm                        |
| <b>Offset</b>                       | 55mm                        |
| <b>Fastening Bolt Hole Diameter</b> | 13mm                        |
| <b>Wheel Bolt Size</b>              | M12                         |
| <b>Bushing Diameter</b>             | 12mm                        |
| <b>Weight</b>                       | 1.67kg                      |
| <b>Wheel Bearing</b>                | double ball bearing         |
| <b>Rubber Shore</b>                 | 65° Shore A                 |


