

## CASTOR HPH98WC200SWS4R0NE



|                                     |                      |
|-------------------------------------|----------------------|
| <b>Product SKU</b>                  | HPH98WC200SWS4R0NE   |
| <b>Standard Compliance</b>          | DIN EN 12532         |
| <b>Series</b>                       | SWS4 (ESD)           |
| <b>Fastening</b>                    | Bolt fastening       |
| <b>Brake and Direction</b>          | swivel without brake |
| <b>Material of the Wheel</b>        | steel wheel center   |
| <b>Tread</b>                        | solid rubber tread   |
| <b>Temperature range</b>            | -20°C to +60°C       |
| <b>Wheel Diameter</b>               | 200mm                |
| <b>Load Capacity</b>                | 140kg                |
| <b>Total Height</b>                 | 228mm                |
| <b>Width of Tread</b>               | 50mm                 |
| <b>wheel hub Width</b>              | 59mm                 |
| <b>Offset</b>                       | 55mm                 |
| <b>Fastening Bolt Hole Diameter</b> | 13mm                 |
| <b>Wheel Bolt Size</b>              | M12                  |
| <b>Bushing Diameter</b>             | 20mm                 |
| <b>Weight</b>                       | 2.89kg               |
| <b>Wheel Bearing</b>                | roller bearing       |
| <b>Rubber Shore</b>                 | 85° Shore A          |
| <b>Special Features</b>             | electrostatic (ESD)  |

