

## CASTOR SHP5EWC200BAY5D0N



|                                  |                               |
|----------------------------------|-------------------------------|
| <b>Product SKU</b>               | SHP5EWC200BAY5D0N             |
| <b>Standard Compliance</b>       | DIN EN 12533                  |
| <b>Series</b>                    | BAY5                          |
| <b>Fastening</b>                 | Plate fastening               |
| <b>Brake and Direction</b>       | swivel without brake          |
| <b>Material of the Wheel</b>     | aluminum wheel center         |
| <b>Tread</b>                     | PU-elastic/polyurethane tread |
| <b>Temperature range</b>         | -20°C to +60°C                |
| <b>Wheel Diameter</b>            | 200mm                         |
| <b>Load Capacity</b>             | 700kg                         |
| <b>Total Height</b>              | 245mm                         |
| <b>Width of Tread</b>            | 50mm                          |
| <b>wheel hub Width</b>           | 60mm                          |
| <b>Offset</b>                    | 55mm                          |
| <b>Dimension of Plate</b>        | 135x110mm                     |
| <b>Hole Spacing of the Plate</b> | 105x84/76mm                   |
| <b>Wheel Bolt Size</b>           | M12                           |
| <b>Bushing Diameter</b>          | 20mm                          |
| <b>Wheel Bearing</b>             | double ball bearing           |
| <b>Rubber Shore</b>              | 75° Shore A                   |

