

## CASTOR SPP57WC250SWS4R0N



|                                  |                      |
|----------------------------------|----------------------|
| <b>Product SKU</b>               | SPP57WC250SWS4R0N    |
| <b>Standard Compliance</b>       | DIN EN 12532         |
| <b>Series</b>                    | SWS4                 |
| <b>Fastening</b>                 | Plate fastening      |
| <b>Brake and Direction</b>       | swivel without brake |
| <b>Material of the Wheel</b>     | steel wheel center   |
| <b>Tread</b>                     | solid rubber tread   |
| <b>Temperature range</b>         | -20°C to +60°C       |
| <b>Wheel Diameter</b>            | 250mm                |
| <b>Load Capacity</b>             | 250kg                |
| <b>Total Hight</b>               | 295mm                |
| <b>Width of Tread</b>            | 50mm                 |
| <b>wheel hub Width</b>           | 59mm                 |
| <b>Offset</b>                    | 65mm                 |
| <b>Dimension of Plate</b>        | 135x110mm            |
| <b>Hole Spacing of the Plate</b> | 105x84/76mm          |
| <b>Wheel Bolt Size</b>           | M12                  |
| <b>Bushing Diameter</b>          | 20mm                 |
| <b>Wheel Bearing</b>             | roller bearing       |
| <b>Rubber Shore</b>              | 85° Shore A          |

