

## CASTOR SSP5SSC160R4E2S34



|                                  |                             |
|----------------------------------|-----------------------------|
| <b>Product SKU</b>               | SSP5SSC160R4E2S34           |
| <b>Standard Compliance</b>       | DIN EN 12532                |
| <b>Series</b>                    | R4E2                        |
| <b>Fastening</b>                 | Plate fastening             |
| <b>Brake and Direction</b>       | swivel without brake        |
| <b>Material of the Wheel</b>     | polyamide (PA) wheel center |
| <b>Tread</b>                     | elastic tread               |
| <b>Temperature range</b>         | -20°C to +80°C              |
| <b>Wheel Diameter</b>            | 160mm                       |
| <b>Load Capacity</b>             | 300kg                       |
| <b>Total Height</b>              | 205mm                       |
| <b>Width of Tread</b>            | 46mm                        |
| <b>wheel hub Width</b>           | 62mm                        |
| <b>Offset</b>                    | 53.5mm                      |
| <b>Dimension of Plate</b>        | 130x74mm                    |
| <b>Hole Spacing of the Plate</b> | 110x50mm                    |
| <b>Wheel Bolt Size</b>           | M12                         |
| <b>Bushing Diameter</b>          | 12mm                        |
| <b>Wheel Bearing</b>             | ball bearing                |
| <b>Rubber Shore</b>              | 65° Shore A                 |
| <b>Special Features</b>          | stainless steel             |

