

## CASTOR TCPESPC100P2Q2B42



|                                  |                                 |
|----------------------------------|---------------------------------|
| <b>Product SKU</b>               | TCPESPC100P2Q2B42               |
| <b>Standard Compliance</b>       | DIN EN 12527                    |
| <b>Series</b>                    | CARA                            |
| <b>Fastening</b>                 | Plate fastening                 |
| <b>Brake and Direction</b>       | back brake                      |
| <b>Material of the Wheel</b>     | polypropylene (PP) wheel center |
| <b>Tread</b>                     | thermoplastic rubber tread      |
| <b>Temperature range</b>         | -20°C to +60°C                  |
| <b>Wheel Diameter</b>            | 100mm                           |
| <b>Load Capacity</b>             | 100kg                           |
| <b>Total Hight</b>               | 140mm                           |
| <b>Width of Tread</b>            | 32mm                            |
| <b>wheel hub Width</b>           | 32mm                            |
| <b>Offset</b>                    | 38mm                            |
| <b>Dimension of Plate</b>        | 77x67mm                         |
| <b>Hole Spacing of the Plate</b> | 61.5/56x51.5/46.5mm             |
| <b>Swivel Radius</b>             | 97mm                            |
| <b>Wheel Bolt Size</b>           | M8                              |
| <b>Bushing Diameter</b>          | 8mm                             |
| <b>Wheel Bearing</b>             | ball bearing                    |
| <b>Rubber Shore</b>              | 85° Shore A/65° Shore A         |





## CASTOR TCPESPC100P2Q2B42

