

## CASTOR TPP37WC125AAX7D0N



|                                  |                       |
|----------------------------------|-----------------------|
| <b>Product SKU</b>               | TPP37WC125AAX7D0N     |
| <b>Standard Compliance</b>       | DIN EN 12532          |
| <b>Series</b>                    | AAX7                  |
| <b>Fastening</b>                 | Plate fastening       |
| <b>Brake and Direction</b>       | back brake            |
| <b>Material of the Wheel</b>     | aluminum wheel center |
| <b>Tread</b>                     | PU-lastic tread       |
| <b>Temperature range</b>         | -20°C to +60°C        |
| <b>Wheel Diameter</b>            | 125mm                 |
| <b>Load Capacity</b>             | 300kg                 |
| <b>Total Hight</b>               | 155mm                 |
| <b>Width of Tread</b>            | 40mm                  |
| <b>wheel hub Width</b>           | 50mm                  |
| <b>Offset</b>                    | 45mm                  |
| <b>Dimension of Plate</b>        | 105x80mm              |
| <b>Hole Spacing of the Plate</b> | 80/77x60mm            |
| <b>Swivel Radius</b>             | 127mm                 |
| <b>Wheel Bolt Size</b>           | M10                   |
| <b>Bushing Diameter</b>          | 15mm                  |
| <b>Wheel Bearing</b>             | double ball bearing   |
| <b>Rubber Shore</b>              | 75° Shore A           |





## CASTOR TPP37WC125AAX7D0N

