

## CASTOR TPP58WC160SWR2R0N



|                                  |                    |
|----------------------------------|--------------------|
| <b>Product SKU</b>               | TPP58WC160SWR2R0N  |
| <b>Standard Compliance</b>       | DIN EN 12532       |
| <b>Series</b>                    | SWR2               |
| <b>Fastening</b>                 | Plate fastening    |
| <b>Brake and Direction</b>       | back brake         |
| <b>Material of the Wheel</b>     | steel wheel center |
| <b>Tread</b>                     | solid rubber tread |
| <b>Temperature range</b>         | -20°C to +60°C     |
| <b>Wheel Diameter</b>            | 160mm              |
| <b>Load Capacity</b>             | 135kg              |
| <b>Total Height</b>              | 195mm              |
| <b>Width of Tread</b>            | 40mm               |
| <b>wheel hub Width</b>           | 59mm               |
| <b>Offset</b>                    | 55mm               |
| <b>Dimension of Plate</b>        | 135x110mm          |
| <b>Hole Spacing of the Plate</b> | 105x84/76mm        |
| <b>Swivel Radius</b>             | 165mm              |
| <b>Wheel Bolt Size</b>           | M12                |
| <b>Bushing Diameter</b>          | 20mm               |
| <b>Weight</b>                    | 2.68kg             |
| <b>Wheel Bearing</b>             | roller bearing     |
| <b>Rubber Shore</b>              | 85° Shore A        |

